

n=2900 rpm

جدول ارتفاع بر حسب آبدهی

آبدهی / Capacity (m ³ /h)								ارتفاع فلکه بسته	موتور Motor (kW)	پمپ Pump
450	400	350**	300	250	200	150	ارتفاع (m)			
-	13	19.5	24	27.5	30	33.5	41	30	466/1a(Ø179/170)	
-	17	23	28	31.5	33	36.5	44	37	466/1a(Ø185/176)	
15	21	27.5	32.5	34	36	39.5	47	37	466/1a(Ø191/182)	
22.5	28.5	33	37	38	40	42	50	45.5	466/1a(Ø197/188)	
27	33.5	39	41	43	45	50	55	55	466/1	
-	29	41.5	50	56.5	61.5	67.5	82	62.5	466/2a(Ø179/170)	
-	36	47.5	57	63	68	73	86	73.5	466/2a(Ø185/176)	
34	45	57.5	67	69.5	73	79.5	94	80	466/2a(Ø191/182)	
18	54	64	72	76	78	84	98	92	466/2a(Ø197/188)	
5	63	73.5	80	83.5	86.5	91.5	106	100	466/2a(Ø203/194)	
57.5	70	80	84	87	91	100	109	110	466/2	
67.5	85	100	112	114.5	120.5	126.5	138	130	466/3a(Ø197/188)	
79	97	112	120.5	123.5	128	135	172	150	466/3a(Ø203/194)	
94	109	123.5	128	132	138	150	196	185	466/3	
119	144	162	171	175	183	200	219	220	466/4	
112	150	166	186	190	200	210	230	220	466/5a(Ø197/188)	
147	174.5	199	204	215.5	224.5	236.5	275	260	466/5a(Ø207/197)	

** It is recommended duty point selected near best efficiency point.

** توصیه می شود نقطه کار پمپ نزدیک به نقطه ماکزیمم راندمان باشد.

جدول ابعاد

قطر نامی سوپاپ Check Valve	وزن کل Total Weight (kg)		Dimentions / ابعاد*				توان نامی / Nom.Power		موتور Motor		پمپ Pump	
			قطر لوله Pipe.Dia (In)	قطر چاه Well.Dia (In)	طول کلی Total Length (mm)		HP	kW				
رزوهی ۸ اینچ / Threaded 8"	338	344	8	12	1970	2000	41	30	9B	9A	466/1a(Ø179/170)	
	349	366	8	12	2020	2100	50	37	9B	9A	466/1a(Ø185/176)	
	349	366	8	12	2020	2100	50	37	9B	9A	466/1a(Ø191/182)	
	371	388	8	12	2120	2200	62	45.5	9B	9A	466/1a(Ø197/188)	
	390	405	8	12	2200	2270	75	55	9B	9A	466/1	
	442	457	8	12	2460	2530	85	62.5	9B	9A	466/2a(Ø179/170)	
	459	481	8	12	2570	2670	100	73.5	9B	9A	466/2a(Ø185/176)	
	470		8	12	2620		109	80	9B		466/2a(Ø191/182)	
	481	522	8	12	2670	2620	125	92	9B	10A	466/2a(Ø197/188)	
	501		8	12	2760		136	100	9B		466/2a(Ø203/194)	
	514	558	8	12	2820	2740	150	110	9B	10A	466/2	
	766	793	8	12	14	2575	3110	177	130	10A	12A	466/3a(Ø197/188)
	818		8	14	3180		204	150	12A		466/3a(Ø203/194)	
	848		8	14	3280		252	185	12A		466/3	
	901	1235	8	14	16	3505	3635	300	220	12B	14B	466/4
	933	1267	8	14	16	3780	3810	300	220	12B	14B	466/5a(Ø197/188)
	1337		8	16	3930		354	260	14B		466/5a(Ø207/197)	

* Ref to page 53

* رجوع شود به صفحه ۵۴