

n=2900 rpm

جدول ارتفاع بر حسب آبدهی

آبدهی / Capacity (m <sup>3</sup> /h)											موتور Motor (kW)	پمپ Pump
580	540	500**	460	420	380	340	300	260	220	ارتفاع فلکه بسته		
ارتفاع / Head (m)												
-	22	26.5	30	34	36	40	42	43	44.5	55	55	486/1a(Ø206/196)
26.5	30	33	36	39	41	43.5	45	45.5	47	57	62.5	486/1a(Ø214/204)
31	34.5	38	40	43	45	47	48	49	50	63	73.5	486/1a(Ø221/211)
33	37.5	41.5	44	47.5	51	53	54	55	56.5	70	80	486/1a(Ø228/218)
36	41	44	47	50	53	53.5	56	57	58	71	92	486/1
-	34	44	50	58	63	69	73	75	77	95	100	486/2a(Ø198/188)
-	48	56.5	63	70.5	74	81.5	85	87	89.5	110	110	486/2a(Ø206/196)
48	57	65	71	77	82	86	88	92	94.5	114	130	486/2a(Ø214/204)
77	85	91.5	97	102	107	109	113	115	117	142	185	486/2
89	101	110.5	120	129	135	141	144	147	150.5	213	220	486/3a(Ø221/211)
116	126	136	144	153	158.5	162	166.5	169	172	229	260	486/3a(Ø233/223)
134	147	161.5	172	182.5	192	199.5	202	205	211	268	300	486/4a(Ø224/214)
137	150	164.5	175.5	186.5	200	210	217.5	223	228	285	300	486/5a(Ø211/201)
150	169	186	196	210	220	230	235	240	245	308	350	486/5a(Ø219/209)

\*\* It is recommended duty point selected near best efficiency point.

\*\* توصیه می شود نقطه کار پمپ نزدیک به نقطه ماکزیمم راندمان باشد.

جدول ابعاد

قطر نامی سوپاپ Check Valve	وزن کل Total Weight (kg)		Dimensions / ابعاد*				توان نامی / Nom.Power		موتور Motor		پمپ Pump	
			قطر لوله Pipe.Dia (In)	قطر چاه Well.Dia (In)	طول کلی Total Length (mm)		HP	kW				
رزوه‌ای ۸ اینچ / Threaded 8"	374	389	10	14	2400	2470	75	55	9B	9A	486/1a(Ø206/196)	
	394	474	10	14	2480	2550	85	62.5	9B	9A	486/1a(Ø214/204)	
	411	433	10	14	2590	2690	100	73.5	9B	9A	486/1a(Ø221/211)	
	422		10	14	2640		109	80	9B		486/1a(Ø228/218)	
	433	474	10	14	2690	2640	125	92	9B	10A	486/1	
	491		10	14	2980		136	100	9B		486/2a(Ø198/188)	
	504	548	10	14	3040	2960	150	110	9B	10A	486/2a(Ø206/196)	
	724	751	10	14	3110	3165	177	130	10A	12A	486/2a(Ø214/204)	
	806		10	14	3335		252	185	12A		486/2	
	865	1199	10	14	16	3660	3790	300	220	12B	14B	486/3a(Ø221/211)
	1269		10	16	3910		354	260	14B		486/3a(Ø233/223)	
	1403		10	16	4260		408	300	14B		486/4a(Ø224/214)	
	1441		10	16	4460		408	300	14B		486/5a(Ø211/201)	
	1505		10	16	4560		476	350	14B		486/5a(Ø219/209)	

\* Ref to page 53

\* رجوع شود به صفحه ۵۴