

n=2900 rpm

جدول ارتفاع بر حسب آبدهی

آبدهی / Capacity (m <sup>3</sup> /h)								موتور Motor (kW)	پمپ Pump
65	60	55	50	45**	40	35	ارتفاع فلکه بسته		
ارتفاع / Head (m)									
22	25	29	32	34	37	38	40.5	7.5	293/2
34	39	45	49	52	55	56	62	11	293/3
48	54	60	66	71	74	76	83	15	293/4
58	67	75	82	87	92	95	104	18.5	293/5
71	81	91	99	106	111	114	124	22	293/6
72	82	92	103	113	117	120	131	22	293/7a(Ø126)
91	104	116	124	130	136	139	143	24.5	293/7
95	108	121	132	141	148	152	165	30	293/8
108	121	135	148	157	164	171	184	30	293/9
118	135	151	165	176	185	190	207	37	293/10
130	149	167	182	194	204	209	225	37	293/11
142	162	182	198	212	222	228	246	45.5	293/12
156	175	195	214	227	238	247	266	55	293/13
165	189	210	231	245	259	266	286	55	293/14
180	202	225	247	262	274	285	306	55	293/15
192	215	240	263	279	289	304	326	62.5	293/16
204	228	255	279	296	304	323	346	62.5	293/17
216	241	270	295	313	319	342	366	73.5	293/18
233	256	285	311	355	351	361	390	73.5	293/19
238	270	300	330	357	368	380	410	80	293/20
248	293	326	346	370	384	399	430	80	293/21

\*\* It is recommended duty point selected near best efficiency point.

\*\* توصیه می شود نقطه کار پمپ نزدیک به نقطه ماکزیمم راندمان باشد.

جدول ابعاد

قطر نامی سوپاپ Check Valve	وزن کل Total Weight (kg)	Dimentions / ابعاد *					Nom.Power / توان نامی *		موتور Motor	پمپ Pump		
		قطر لوله Pipe.Dia (In)	قطر چاه Well.Dia (In)	طول کلی Total Length (mm)		HP	kW					
رزه‌ای ۳ اینچ / Threaded 3"	104	4	10	1580		10	7.5	6E	293/2			
	139	4	10	1650		15	11	7A	293/3			
	157	4	10	1815		20	15	7A	293/4			
	178	4	10	1960		25	18.5	7A	293/5			
	190	4	10	2075		30	22	7A	293/6			
	196	4	10	2140		30	22	7A	293/7a(Ø126)			
	243	270	4	10	12	2360	2205	33	24.5	8A	9A	293/7
	285	291	4	12	2310		2340	41	30	9B	9A	293/8
	291	297	4	12	2375		2405	41	30	9B	9A	293/9
	308	325	4	12	2490		2570	50	37	9B	9A	293/10
	314	331	4	12	2555		2635	50	37	9B	9A	293/11
	342	359	4	12	2720		2800	62	45.5	9B	9A	293/12
	367	382	4	12	2865		2935	75	55	9B	9A	293/13
	373	388	4	12	2930		3000	75	55	9B	9A	293/14
	379	394	4	12	2995		3065	75	55	9B	9A	293/15
	411	426	4	12	3205		3275	85	62.5	9B	9A	293/16
	417	432	4	12	3270		3340	85	62.5	9B	9A	293/17
	440	462	4	12	3450		3550	100	73.5	9B	9A	293/18
	446	468	4	12	3510		3610	100	73.5	9B	9A	293/19
	463		4	12	3625			109	80	9B		293/20
	469		4	12	3690			109	80	9B		293/21

\* Ref to page 53

\* رجوع شود به صفحه ۵۳