

PW



### Application Limits

- Suction lift up to 8 m
- Max. working pressure 5 bar
- Liquid temperature up to +90°C
- Ambient temperature up to +40°C
- Voltage fluctuations should not exceed 10% of rate value

### Advantages & Features

- Compact design, easy installation
- A simple Pressure switch control automatically
- Pump body insert of stainless sheet 304
- Shaft extension is stainless steel 304
- The impeller of copper alloy
- High quality mechanical seal

### Performance Data

Model	Power		Max. Flow (m <sup>3</sup> /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L × W × H(mm)	G.W (kg)	20'Loading Qty. (pcs)	
	Single-Phase	kW								HP
PW125		0.125	0.17	2	24	1-20	8	295 × 230 × 305	8.3	1600
PW250		0.25	0.34	2.2	30	1-26	8	295 × 230 × 305	9.0	1600
PW370		0.37	0.5	2.4	36	1-32	8	295 × 230 × 305	9.3	1600
PW550		0.55	0.75	3.0	42	1.5-38	8	315 × 245 × 325	12.1	1320
PW750		0.75	1	3.4	50	1.5-46	8	315 × 245 × 325	13.8	1320
PW1100		1.1	1.5	6	55	1.5-51	8	365 × 280 × 380	21.7	720
PW1100L		1.1	1.5	6	55	1.5-51	8	515 × 320 × 640	26.3	260

Note: The cable length of single phase pump is 1.3m, Europe plug.