

CPm



Application Limits

- Suction head up to 7m
- Liquid temperature up to +40°C
- Ambient temperature up to +40°C
- Max. Working pressure: 6bar
- Voltage fluctuation should not exceed 10% of rated value.
- pH: 6.5 to 8.5

Advantages & Features

- Single suction centrifugal pump, with high efficiency
- Copper impeller, stable performance
- High head, small flow rate

Performance Data

Model	Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L × W × H(mm)	G.W (kg)	20'Loading Qty. (pcs)
	kW	HP							
CPm130	0.37	0.5	6	22	11~22	7	285 × 185 × 230	9	2480
CPm146	0.55	0.75	6.6	26	12~26	7	340 × 210 × 265	12	1683
CPm158	0.75	1	7.2	32	13~32	7	340 × 210 × 265	14	1683
CPm170	1.1	1.5	7.8	40	25~40	7	390 × 240 × 290	21	1152
CPm190	1.5	2	7.8	48	31~48	7	390 × 260 × 320	24.5	945
CPm200	2.2	3	8.4	55	23~55	7	455 × 280 × 340	33.5	735

Note: The length of cable is 0.3m, no plug.