



QB



QB60L/K



Application Limits

- ⊙ Suction head up to 8m
- ⊙ Liquid temperature up to +40°C
- ⊙ Ambient temperature up to +40°C
- ⊙ Max. Working pressure: 6bar
- ⊙ Voltage fluctuation should not exceed 10% of rated value.
- ⊙ pH: 6.5 to 8.5

Advantages & Features

- ⊙ Small size, high pressure
- ⊙ Easy installation & maintenance

Performance Data

Model	Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. (L×W×H) mm	G.W. (kg)	20'Loading Qty. (pcs)
	kW	HP							
QB60	0.37	0.5	2.4	33	1~27	8	275×128×160	5	4710
QB60-1	0.37	0.5	2.4	35	2~29	8	275×128×160	5	4710
QB70	0.55	0.75	3	48	1.5~44	8	335×190×210	8.5	2076
QB80	0.75	1	3.6	60	2.5~53	8	345×190×210	10	2064
QB60L	0.37	0.5	2.4	33	1~27	8	235×135×175	4.3	4800
QB60K	0.37	0.5	2.4	40	1.5~30	8	235×135×175	4.7	4800