

Submersible & Sewage Pump

WQ(D)S Submersible Pump For Dirty water

Application Limits

- Maximum liquid temperature +40°C
- pH level from 4-10
- Maximum liquid density $1.2 \times 10^3 \text{ kg/m}^3$
- Power frequency is 50Hz. Nominal voltage is 220VAC for single phase and 380VAC for three phase with tolerance of $\pm 10\%$.
- Immersion depth from 0.5m-5m

Advantages & Features

- Stainless steel motor case for beauty and durability
- Open impeller for easier passage of suspended solid
- The stainless steel shaft extension, carbide double sides mechanical sealing



WQ(D)S

Performance Data

Model		Power		Rate Current (A)	Solids Passage (mm)	Max.Flow (m ³ /h)	Max.Head (m)	Head Range (m)	Cable line (m)	Dim.mm (L×W×H)	G.W. (kg)	20' Loading Qty. (pcs)
Single-Phase	Three-Phase	kW	HP									
WQDS7-7-0.55	-	0.55	0.75	4.1	25	20	8	5~8	3*0.75-5	540×215×295	26	864
WQDS7-7-0.55A	-	0.55	0.75	4.1	43	20	8	5~8	3*0.75-5	580×215×300	26	756
WQDS10-7-0.75	-	0.75	1	5.2	25	25	10	5~9	3*1-5	580×215×295	28	864
WQDS10-7-0.75A	-	0.75	1	5.2	43	21	9	5~9	3*1-5	600×215×300	30	630
WQDS10-10-1.1	-	1.1	1.5	7.3	25	28	12	7~12	3*1-5	580×215×295	30	864
WQDS10-10-1.1A	-	1.1	1.5	7.3	45	29	13	7~12	3*1-10	585×215×300	30	756
WQDS15-9-1.1CB	-	1.1	1.5	7.3	20	25	15	5~12	3*1-10	595×235×320	30	630
WQDS15-10-1.5	-	1.5	2	9.5	35	30	14	5~12	3*1.5-10	600×215×300	32	630
WQDS25-7-1.5CB	-	1.5	2	9.5	20	36	17	5~13	3*1.5-10	610×235×320	32	630
-	WQS10-7-0.75A	0.75	1	2	43	21	9	5~9	4*0.75-10	625×210×325	28	693
-	WQS10-9-0.75CB	0.75	1	2	20	23	12	7~11	4*0.75-10	580×215×295	28	864
-	WQS10-10-1.1	1.1	1.5	2.7	28	28	12	7~12	4*0.75-10	585×215×300	29	756
-	WQS15-9-1.1CB	1.1	1.5	2.7	20	25	15	5~12	4*0.75-10	595×235×320	29	630
-	WQS15-10-1.5	1.5	2	3.6	25	30	14	5~12	4*0.75-10	600×215×300	32	630
-	WQS25-7-1.5CB	1.5	2	3.6	20	36	17	5~13	4*0.75-10	610×235×320	31	630