

**WSD Submersible Pump
 For Dirty water**



WSD

Application Limits

- ⊙ Maximum liquid temperature +40°C
- ⊙ pH level from 4-10
- ⊙ Passage of suspended solids up to 50mm
- ⊙ Power frequency is 50Hz.Voltage fluctuation range ± 10%

Advantages & Features

- ⊙ External components of SS304 material which is corrosion-resistant.
- ⊙ Vortex impeller with larger passage of suspended solid.
- ⊙ Automatic operation for the floating switch.

Performance Data

Model	Power		Rate Current (A)	Solids Passage (mm)	Max.Flow (m ³ /h)	Max.Head (m)	Head Range (m)	Cable line (m)	Dim.mm (L×W×H)	G.W. (kg)	20' Loading Qty. (pcs)
	kW	HP									
WSD55/50	0.55	0.75	4.2	50	17	7.5	4~6	3*1.0-5	230×200×465	10.5	1420
WSD55/50T	0.55	0.75	4.2	50	16	7.5	4~6	3*1.0-5	230×200×465	13.5	1420
WSD75/50	0.75	1	5.2	50	20	9.5	4~7	3*1.0-5	230×200×465	11	1420
WSD75/50T	0.75	1	5.2	50	20	9.5	4~9	3*1.0-5	230×200×465	14.5	1420
WSD55/35	0.55	0.75	4.2	35	18	8.5	4~6	3*1.0-5	230×200×465	10	1420
WSD55/35T	0.55	0.75	4.2	35	18	8	4~6	3*1.0-5	230×200×465	13	1420
WSD75/35	0.75	1	5.2	35	22	10	4~7	3*1.0-5	230×200×465	11	1420
WSD75/35T	0.75	1	5.2	35	22	9.5	4~9	3*1.0-5	230×200×465	14	1420