

● **Technical data and dimensions(Installation drawing is same as WQ)**

Model	Q	H	Speed	Power	Current	Max. dia. of passing solid (mm)	Dimensions(mm)										Weight (kg)
	(m ³ /h)	(m)	(rpm)	(kW)	(A)		H	H1	B3	B2	D2	d	D	D1	n1-φ d1		
50WQ7-7-0.55F	7	7	2860	0.55	1.6	15	430	300	330	230	190	50	140	110	4-φ14	18	
50WQ5-10-0.55F	5	10	2860	0.55	1.6	15	430	300	330	230	190	50	140	110	4-φ14	18	
50WQ10-7-0.75F	10	7	2860	0.75	2.0	20	430	300	330	230	190	50	140	110	4-φ14	18	
50WQ7-10-0.75F	7	10	2860	0.75	2.0	20	430	310	330	230	190	50	140	110	4-φ14	18	
50WQ15-8-1.1F	15	8	2860	1.1	2.8	20	430	310	330	230	190	50	140	110	4-φ14	20	
50WQ8-15-1.1F	8	15	2860	1.1	2.8	20	430	310	330	230	190	50	140	110	4-φ14	20	
50WQ15-10-1.5F	15	10	2860	1.5	4.0	20	485	330	350	250	200	50	140	110	4-φ14	28	
50WQ10-15-1.5F	10	15	2860	1.5	4.0	20	485	330	350	250	200	50	140	110	4-φ14	28	
50WQ25-10-2.2F	25	10	2860	2.2	6.0	25	485	345	350	250	200	50	140	110	4-φ14	30	
50WQ15-15-2.2F	15	15	2860	2.2	6.0	20	485	345	350	250	200	50	140	110	4-φ14	30	
50WQ9-22-2.2F	9	22	2860	2.2	6.0	20	485	345	350	250	200	50	140	110	4-φ14	30	
50WQ25-15-3F	25	15	2860	3	6.5	20	510	400	370	270	200	50	140	110	4-φ14	37	
50WQ25-22-4F	25	22	2860	4	8.4	25	600	440	380	280	250	50	140	110	4-φ14	48	
50WQ30-32-7.5F	30	32	2860	7.5	16.8	25	640	500	440	346	320	50	160	130	4-φ14	63	
65WQ35-8-2.2F	35	8	2860	2.2	6.0	25	485	345	380	250	200	65	160	130	4-φ14	30	
65WQ35-10-3F	35	10	2860	3	6.5	25	520	420	400	270	200	65	160	130	4-φ14	37	
65WQ40-15-4F	40	15	2860	4	8.4	30	610	440	410	280	250	65	160	130	4-φ14	48	
65WQ30-22-5.5F	30	22	2860	5.5	12.0	25	630	470	420	290	250	65	160	130	4-φ14	55	
80WQ50-8-3F	50	8	2860	3	6.5	30	520	420	400	270	200	76	190	150	4-φ18	37	
80WQ50-10-4F	50	10	2860	4	8.4	30	610	440	410	280	250	76	190	150	4-φ18	48	
80WQ65-15-5.5F	65	15	2860	5.5	12.0	30	630	470	420	290	250	76	190	150	4-φ18	55	
80WQ45-22-7.5F	45	22	2860	7.5	16.8	30	650	490	440	310	290	76	190	150	4-φ18	68	
100WQ65-10-4F	65	10	2860	4	8.4	30	610	440	440	280	250	100	210	170	4-φ18	48	
100WQ100-8-5.5F	100	8	2860	5.5	12.0	35	640	480	420	290	250	100	210	170	4-φ18	58	
100WQ80-15-7.5F	80	15	2860	7.5	16.8	30	660	500	460	310	290	100	210	170	4-φ18	73	
100WQ100-10-7.5F	100	10	2860	7.5	16.8	35	660	500	460	310	290	100	210	170	4-φ18	73	

e