

Features

Powerful multistage submersible pump ideal for rainwater systems, operating sprinklers, pumping water from cisterns, tanks, ponds, wells and other applications that require high pressure.

Motor with thermal protector.

Multistage Impeller Technology



Stainless Steel Filter

Model	LKS-900S	LKS-1100S	LKS-1300S
Rated Power	900 W	1100 W	1300 W
Max. Head	32 m	42 m	52 m
Max. Flow	7 m ³ /h	7 m ³ /h	7 m ³ /h
Max. Depth of Immersion	7 m	7 m	7 m
Max. Dia. of Particle	1 mm	1 mm	1 mm
Outlet	1"	1"	1"
Power Cable Type	H07RN-F	H07RN-F	H07RN-F
Length of Power Cable	10 m	10 m	10 m
Protection Class	IPX8	IPX8	IPX8
Impellers	3	4	5
Max. liquid Temperature	35 °C	35 °C	35 °C
Qty in carton box	1 pcs	1 pcs	1 pcs
Package Dimension	480×250×210 mm	502×250×210 mm	527×250×210 mm
Package Gross Weight	11.2 kg	12.3 kg	13.2 kg
Qty/20'GP	920	880	880
Automatic function	Float Switch	Float Switch	Float Switch

Features

With built-in integrated electronics, designed to automatically start and stop the pump.

Compact, easy to use, with dry-running protection and built-in check valve.

Motor with thermal protector.



LKS-02SE

LKS-02SE-1

Model	LKS-902SE	LKS-1102SE	LKS-902SE-1	LKS-1102SE-1
Rated Power	900 W	1100 W	900 W	1100 W
Max. Head	35 m	45 m	35 m	45 m
Max. Flow	6 m ³ /h	6 m ³ /h	6 m ³ /h	6 m ³ /h
Max. Depth of Immersion	12 m	12 m	12 m	12 m
Max. Dia. of Particle	1 mm	1 mm	1 mm	1 mm
Outlet	1"	1"	1"	1"
Power Cable Type	H07RN-F	H07RN-F	H07RN-F	H07RN-F
Length of Power Cable	15 m	15 m	15 m	15 m
Protection Class	IPX8	IPX8	IPX8	IPX8
Impellers	3	4	3	4
Max. liquid Temperature	35 °C	35 °C	35 °C	35 °C
Qty in carton box	1 pcs	1 pcs	1 pcs	1 pcs
Package Dimension	260×215×540 mm	260×215×565 mm	260×215×540 mm	260×215×565 mm
Package Gross Weight	10.4 kg	11.6 kg	10.4 kg	11.6 kg
Qty/20'GP	928	880	928	880
Automatic function	aquasensor	aquasensor	aquasensor	aquasensor



With a cable holder for the float switch, the cut-in and cut-out heights can be precisely and flexibly adjusted.



Position adjustable handle

Features

Automatic operation for comfortable handling, the on-off function is controlled by the adjustable float switch automatically.

Long service life and problem-free operation thanks to the low-wear feed impeller and robust housing.

Motor with thermal protector.

High quality and robust housing made of stainless steel

Motor with thermal protector

Robust stainless steel base



Particles Diameter up to 35mm

Model	LKS-558SW	LKS-758SW	LKS-1008SW
Rated Power	550 W	750 W	1000 W
Max. Head	6 m	7 m	10.5 m
Max. Flow	12 m ³ /h	14 m ³ /h	19.5 m ³ /h
Max. Depth of Immersion	7 m	7 m	7 m
Max. Dia. of Particle	35 mm	35 mm	35 mm
Outlet	1 1/2"	1 1/2"	1 1/2"
Power Cable Type	H05RN-F	H07RN-F	H07RN-F
Length of Power Cable	10 m	10 m	10 m
Protection Class	IPX8	IPX8	IPX8
Max. liquid Temperature	35 °C	35 °C	35 °C
Qty in carton box	4 pcs	4 pcs	4 pcs
Package Dimension	450×350×375 mm	450×350×375 mm	450×350×387 mm
Package Gross Weight	28 kg	30 kg	33 kg
Qty/20'GP	1540pcs	1540pcs	1540pcs
Automatic function	Float Switch	Float Switch	Float Switch



Position adjustable handle



With a cable holder for the float switch, the cut-in and cut-out heights can be precisely and flexibly adjusted.

Features

Suitable for pumping dirty water containing particles with maximum diameter up to 35mm.

Float switch ensures automatic start and stop.

Motor with thermal protector.

Adjustable Handle

Easy and reliable positioning of the float in different positions.

High-Quality and Robust Stainless Steel Housing

Particles Diameter up to 35mm



Model	LKS-758PSW
Rated Power	750 W
Max. Head	9 m
Max. Flow	17 m ³ /h
Max. Depth of Immersion	7 m
Max. Dia. of Particle	35 mm
Outlet	1 1/2"
Power Cable Type	H07RN-F
Length of Power Cable	10 m
Protection Class	IPX8
Max. liquid Temperature	35 °C
Qty in carton box	4 pcs
Package Dimension	510×450×370 mm
Package Gross Weight	28.3 kg
Qty/20'GP	1152
Automatic function	Float Switch